

XM-3015W



The FEC new generation product – Xmonitor, which redesigned with XPPC, provides three different installation methods. Respectively is the integrated type mounted on the monitor, the arm type fixed on the stand, and the pole type with an independent extending FEC pole.

For more information, contact us at sales@mai.hr



01/ 2nd Monitors Arm type



02/ 2nd Monitors Pole Type

15" | 15.6"




03/ 2nd Monitors

Arm Type / Integrated Type / Pole Type



Spec.



Display

- 15.6" TFT , 1920 x 1080



Brightness

- 300 nits



Speaker

- 4ohm 2W (Available for AD board Version)



Mounting

- Standalone
- Arm Type
- Pole Type
- VESA 100 x 100 mm



Appearance

- Aluminum Die-casting + Plastic
- Galaxy Grey



Dimensions (W x H x D)

- Product: 368 x 272.5 x 315 mm
- Carton: 492 x 168 x 488 mm



Touch

- Non-Touch
- True-Flat PCAP



MTBF

- 50K Hours



Power

- AD board Version:
12V DC-in (Power From VGA, USB DP)
- SMART DD Version:
20V DC-in (Power From SMART DD)



Certification

- FCC / CE Class B



Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 140 °F)



Weight

- Display Only (Net): 3 Kg
- Display with Stand (Net): 3.9 Kg
- Display with Stand (Gross): 5.6 Kg



Port

- AD board Version:
 - 1 x Video Port
 - 1 x VGA (12V Power)
 - 1 x USB DP
 - 1 x USB 2.0 Type B
 - 1 x DC-in 12V
 - 1 x Line-in
- Smart DD Version:
 - 1 x Smart DD in
 - 1 x Smart DD out



Optional

- Compatible with XPOS Add-on device(Supports Device on Right Side)
- 2 in 1 Sensor (Ambient Light, Proximity)
- 2MP Front Camera
- 2 x USB 2.0 Type A