KP-9795W

Resilience Through Heat, Precision Under Pressure

FEC

KP: KEEN PERMANENCE

RESILIENCE THROUGH HEAT, PRECISION UNDER PRESSURE

KP-9795W / KP-9155W

SPLASH IT. DUST IT. IT STILL WORKS.

0°C - 50°C, RUNS COLD. RUNS HOT.



WET HAND / GLOVE OPERATION

POWER OVER ETHERNET
ONE CABLE SOLUTION

MTK250919KDSKPV23

Copyright © 2025 Firich Enterprises Co., Ltd. All Rights Reserved

For more information, contact us at sales@mai.hr

FEC

KP *SPECIFICATIONS*

Model	*KP-9795W*	*KP-9155W*
Processor	**Intel** N97/N150/Core 3 N355	**MTK** G700
Memory	1 x DDR4 SO-DIMM Socket (Standard 4G, up to 16GB)	1 x DDR4 8G on Board
Storage	1 x M.2 2280 SSD PCIe Gen 3x4 (Standard 128G, up to 512G)	1 x eMMC 64G on Board
Speak	2 x 2W	2 x 2W
Display	15.6" TFT, 1920 x 1080	15.6" TFT, 1920 x 1080
Brightness	350 / 500 nits	350 / 500 nits
Touch	P-CAP (Support Water-resistant & Glove Mode)	P-CAP (Support Water-resistant & Glove Mode)
OS	Windows 10 IoT Enterprise, Windows 10 Pro, Windows 11 IoT Enterprise, Windows 11 Pro, Linux by Request	Android 14
Mounting	VESA 75 x 75 mm	VESA 75 x 75 mm
Certification	FCC, CE Class B	FCC, CE Class B
Construction/Color	Aluminum Die-Casting + Plastic / Grey	Aluminum Die-Casting + Plastic / Grey
Temperature	Operation: 0˚C ~ 50˚C (32˚F ~ 122˚F)	Operation: 0˚C ~ 50˚C (32˚F ~ 122˚F)
	Storage: -20˚C ~ 60˚C (-4˚F ~ 140˚F)	Storage: -20˚C ~ 60˚C (-4˚F ~ 140˚F)
IO Port	1 x 19V DC-in 1 x RJ45 GIGA LAN (Support PoE Function) 3 x USB 2.0 Type-A 1 x USB 3.0 Type-A 1 x RJ45 COM (RS232) 	1 x 19V DC-in 1 x RJ45 GIGA LAN (Support PoE Function) 3 x USB 2.0 Type-A 1 x USB 3.0 Type-A 1 x SD Card Slot 1 x USB OTG Type-C 1 x Recovery Button
IP Rating	IP54 (All-Device)	IP54 (All-Device)
Power	19V/65W Adapter	19V/65W Adapter
Dimensions (W x H x D)	316.7 x 219.7 x 14.5 mm in Carton : 460 x 370 x 36.4 mm	316.7 x 219.7 x 14.5 mm in Carton : 460 x 370 x 36.4 mm
Weight	Net: 2.8 kg Gross: 4.1 kg	Net: 2.7 kg Gross: 4.1 kg
Optional	Options: PoE PD Module 24V/60W Wi-Fi Module (Internal) Peripherals Options: Scanner / RFID / LED Bar / Camera	Options: PoE PD Module 24V/60W Wi-Fi Module (Internal) Peripherals Options: Scanner / RFID / LED Bar / Camera

Built to withstand harsh environments

For more information, contact us at sales@mai.hr

MAI Solutions