



**NQuire
Accessories**
micro kiosk

FEATURES

Multifunctional Configuration.

An RFID module, 4G module and magnetic strip card reader module are great accessories to compliment the NQuire series and meet a variety of application needs.

Integrated Design.

Perfectly suited for the NQuire 1000 Manta and the NQuire 750 Sting Ray, these accessories are easily mounted and transported.

Application Scenarios

Accessories compatible with the NQuire 1000 Manta and NQuire 750 Sting Ray

RFID/4G/Card Module

RFID Module



| | 13.56M NFC Module | 125K Module |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocol | Comply with ISO14443A/B protocol, such as MIFARE, NFC Forum Tags (NFC Forum Tags only partially support 14443A/B protocol), second-generation ID cards, bus cards, bank cards, social security cards, access cards, membership cards and other cards that meet this standard. | Read only low frequency ID card: EM4200 (and other universal compatible cards) Read/write low frequency card: EM4305 (and other universal compatible cards) |
| Operation Distance | 0-3cm | 0-3cm |
| Power Consumption | Operating current: 300ma Maximum current: 400ma | Operating current: 100ma Maximum current: 350ma |
| Weight | 35.5g | 33.2g |
| Dimension | 71mm(length)×59mm(width)×22mm(height) | 71mm(length)×59mm(width)×22mm(height) |
| Operating Temperature | -10℃~50℃ | -10℃~50℃ |
| Storage Temperature | -20℃~60℃ | -20℃~60℃ |
| Certification | FCC,CE,ROHS | FCC,CE,ROHS |

4G-LTE Module



| | |
|-----------------------|-------------------------------------------------------------|
| System | FDD LTE :B1/B3/B7/B8/B20/B28A WCDMA :B1/B8 GSM :B3/B8 |
| Power Consumption | Operating current: 100ma Maximum current: 2.5A |
| SIM Card | Micro SIM |
| Weight | 35.5g |
| Dimension | 71mm(length)×58mm(width)×22mm(height) |
| Operating Temperature | 5℃~50℃ |
| Storage Temperature | -10℃~60℃ |
| Certification | FCC,CE,ROHS |

MSR Module



| | |
|-----------------------|---------------------------------------------------|
| Protocol | Comply with ISO/IEC 7811-2 Card |
| Track | Support three-track magnetic stripe card decoding |
| Reversible Read | Both two side of the card can be read |
| Power Consumption | Operating current: 50ma Maximum current: 80ma |
| Weight | 41g |
| Dimension | 71mm(length)×43mm(width)×29mm(height) |
| Operating Temperature | -10℃~50℃ |
| Storage Temperature | -20℃~60℃ |
| Certification | FCC,CE,ROHS |