

# XM-3015



The FEC new generation product – Xmonitor, which redesigned with XPPC, provides three different installation methods. Respectively is the integrated type mounted on the monitor, the arm type fixed on the stand, and the pole type with an independent extending FEC pole.

For more information, contact us at [sales@mai.hr](mailto:sales@mai.hr)

---



## 01/ 2nd Monitors Arm type



## 02/ 2nd Monitors Pole Type

15" | 15.6"




## 03/ 2nd Monitors

Arm Type / Integrated Type / Pole Type



# Spec.



## Display

- 15" TFT , 1024 x 768



## Brightness

- 350 nits



## Speaker

- 4ohm 2W (Available for AD board Version)



## Mounting

- Standalone
- Arm Type
- Pole Type
- VESA 100 x 100 mm



## Appearance

- Aluminum Die-casting + Plastic
- Galaxy Grey



## Dimensions (W x H x D)

- Product: 342 x 310 x 342 mm
- Carton: 448 x 156 x 468 mm



## Touch

- Non-Touch
- True-Flat PCAP



## MTBF

- 50K Hours



## Power

- AD board Version:  
12V DC-in (Power From VGA, USB DP)
- SMART DD Version:  
20V DC-in (Power From SMART DD)



## Certification

- FCC / CE Class B



## Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 140 °F)



## Weight

- Display Only (Net): 3 Kg
- Display with Stand (Net): 3.9 Kg
- Display with Stand (Gross): 5.6 Kg



## Port

- AD board Version:
  - 1 x Video Port
  - 1 x VGA (12V Power)
  - 1 x USB DP
  - 1 x USB 2.0 Type B
  - 1 x DC-in 12V
  - 1 x Line-in
- Smart DD Version:
  - 1 x Smart DD in
  - 1 x Smart DD out



## Optional

- Compatible with XPOS Add-on device(Supports Device on Right Side)
- 2 in 1 Sensor (Ambient Light, Proximity)
- 2MP Front Camera
- 2 x USB 2.0 Type A