

NCR XL15W Wide-Aspect Display

Uncommon value in a retail-hardened PCAP display

Your stores reflect your brand image, so you want your checkout areas to be as inviting as possible to your shoppers. NCR's sleek ultra-thin XL15W display offers the look you need — and at a price that will fit your budget.

Tap, zoom, swipe, or scroll

This projected capacitive (PCAP) display supports multi-touch interactions and gestures, making it familiar and easy for your associates to use. Another advantage: The XL15W needs no initial or ongoing calibration, avoiding unnecessary service calls.

Make a smart choice

You know that retail is hard on point-of-sale equipment. This display was designed from scratch for demanding store environments, so its sleek lines provide much more than just a pretty face. The XL15W resists dust and liquid and — especially important today — its flush zero-bezel surface makes this display very easy and quick to clean.

On-screen software controls prevent tampering or accidental shutdown, plus eliminating buttons and switches to maintain the smooth look of your POS. And the screen is exceptionally bright and sharp with the outstanding readability to create an enjoyable experience for your customers and associates.

Flexibility without compromise

The XL15W display can be positioned on its own display stand, a wall, pole or other custom mounting using a standard VESA mount. The XL15W is available with an optional integrated RFID reader or secure encrypted magnetic stripe reader, as well as a variety of latching USB, Display Port and audio cables.

This ultra-thin display is sure to enhance your checkout or wrap-stand while maximizing your counter space.

Key features

- Wide-aspect 16:9 display (1920 x 1080) with PCAP touch
- Zero-bezel design for sleek good looks and easy cleaning, with 10-point multi-touch support
- LED backlight with anti-glare surface
- Multiple mounting options including stands and VESA conformity for pole, wall or other custom mounting
- Retail-hardened design, resistant to dust and liquid spills
- Touch screen supports conductive/capacitive stylus and many types of thin gloves
- An NCR product with proven quality you can trust. We offer a full range of service programs to protect your investment and enhance your business, including NCR's anti-microbial coating service, available for this display.



To speak with someone or for more information, visit us at [ncr.com](https://www.ncr.com).



Engineered for demanding retail environments

The XL15W carries forward NCR's rich heritage of innovation, adaptability, unrelenting toughness and sheer capability. Its performance and flexibility will uniquely serve your business.

Just as with our flagship POS terminals, NCR spares no effort and overlooks no detail in building our POS peripherals: From the ground-up the XL15W was purpose-built to handle the rigors of retail. Its enclosure was engineered to prevent dust and liquid incursion, as well as internal hot spots that might lead to compromised performance or failures. All materials — down to component level — have been carefully chosen for long life cycles and reliability.

Then to prove it all, the XL15W was subjected to NCR's severe battery of environmental, ESD, power, electromagnetic radiation and reliability tests.

Combining all these exacting requirements with further long-run environmental and compatibility testing exceeds the usual industry and regulatory standards, but it leads to your XL15W displays delivering years and years of dependable operation.

Technical specifications

Display and Screen

- Aspect ratio: 16:9 (widescreen)
- Native resolution: 1920x1080
- Touch technology: Projected capacitive (10-point multi-touch)
- Non-touch option: Yes
- Backlight type: LCD
- Contrast ratio: 800:1
- Display surface: Anti-glare

Power and connections

- Video interface: Display Port
- Audio interface: Integrated speaker (non-amplified, audio cable required)
- Power: 1x8 latching 12V P-USB (+Power) from POS or external power supply

Mounting options

- NCR counter top stand
- NCR integrated mount (VESA 100 mm x 100 mm)

Options

- Encrypted MSR
- RFID reader
- Terminal stand

User environment

- Operating temperature: 0°C to 40°C (32°F to 104°F)
- Humidity: 10% to 90% relative humidity, non-condensing
- Environmental sealing: IPX3

Physical characteristics

- Dimensions (display only; W x D x H):
383 mm (15.08 in) x 35 mm (1.38 in) x 240 mm (9.45 in)
Weight: 2.1kg (4.55 lbs)
- Dimensions (display on stand; W x D x H):
383 mm (15.08 in) x 244 mm (9.6 in) x 296 mm (11.7 in)
Weight: 4.15 kg (9.15 lbs)

Warranty and service

- One-year NCR depot (where available – check with NCR)
- NCR anti-microbial coating/service

Why NCR?

NCR Corporation (NYSE: NCR) is a leading software and services-led enterprise provider in the financial, retail, hospitality, small business and telecom and technology industries. We run key aspects of our clients' business so they can focus on what they do best.

NCR is headquartered in Atlanta, GA with 34,000 employees and solutions in 141 countries. NCR is a trademark of NCR Corporation in the United States and other countries.

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2020 NCR Corporation Patents Pending

061020_PMM-RET ncr.com

